



Light**FEEL**


@LIGHTFEEL.COM

# Smart switch Catalog

NEW PRODUCT YEAR 2024




# Smart Home for Whole House



 Works with **Amazon Alexa**

 Works with **Google Assistant**





# L7

# ZIGBEE Smart Switch

## WI-FI & ZIGBEE SMART SWITCH

WITH THE MOST ADVANCED ZIGBEE + WIFI  
TECHNOLOGY LANBON SMART LIVING  
SERVERS YOUR MODERN LIFE



&



# L7 Light Switch (1GANG/2GANG/3GANG)

## 1-GANG



L7-HS1-B(Black)



L7-HS1-W(White)

## 2-GANG



L7-HS2-B(Black)



L7-HS2-W(White)

## 3-GANG




L7-HS3-B(Black)




L7-HS3-W(White)

wiring diagram



size diagram



### Specification

Size:	85×85×32mm	Rated Load:	200W/GANG
Item no:	L7-HS1/2/3	Load type:	Incandescent lamp, energy saving lamp, fluorescent
Weight:	0.3kg	Wireless standards:	IEEE 802.15.4
Packing box size:	141×103×47mm	Frequency range:	2.405GHz~2.480GHz
Panel:	Tempered Crystal Glass	Receiving sensitivity:	-97dBm@250kbps
Bottom Materials:	Retardant PC	Operating temperature:	-25 degree to +60 degree
Rated voltage:	AC 100-250V 50/60Hz	Relative humidity:	<95%

package



# L7 Light Switch (1GANG/2GANG/3GANG)

## 1-GANG



L7-HSU1-B(Black)



L7-HSU1-W(White)

## 2-GANG



L7-HSU2-B(Black)



L7-HSU2-W(White)

## 3-GANG




L7-HSU3-B(Black)




L7-HSU3-W(White)

wiring diagram



size diagram



### Specification

Size:	120×74×32mm	Rated Load:	200W
Item no:	L7-HSU1/2/3	Load type:	Incandescent lamp, energy saving lamp, fluorescent
Weight:	0.3kg	Wireless standards:	IEEE 802.15.4
Packing box size:	141×103×47mm	Frequency range:	2.405GHz~2.480GHz
Panel:	Tempered Crystal Glass	Receiving sensitivity:	-97dBm@250kbps
Bottom Materials:	Retardant PC	Operating temperature:	-25 degree to +60 degree
Rated voltage:	AC 100-250V 50/60Hz	Relative humidity:	<95%

package



# L7 Dimmer Light Switch



L7-HD-B(Black)



L7-HD-W(White)



L7-HDU-B(Black)




L7-HDU-W(White)


## Specification

Size:	85×85×32mm/120×74×32mm	Rated Load:	200W
Item no:	L7-HD/L7-HDU	Load type:	LED light , Incandescent Lamp
Weight:	0.3kg	Wireless standards:	IEEE 802.15.4
Packing box size:	141×103×47mm	Frequency range:	2.405GHz~2.480GHz
Panel:	Tempered Crystal Glass	Receiving sensitivity:	-97dBm@250kbps
Bottom Materials:	Retardant PC	Operating temperature:	-25 degree to +60 degree
Rated voltage:	AC 100-250V 50/60Hz	Relative humidity:	<95%

## wiring diagram



## size diagram



## package



# L7 Scene Switch



L7-HE-B(Black)



L7-HE-W(White)



L7-HEU-B(Black)




L7-HEU-W(White)


## Specification

Size:	85×85×32mm/120×74×32mm	Rated Load:	0.25W
Item no:	L7HE/L7-HEU	max scene:	3
Weight:	0.3kg	Wireless standards:	IEEE 802.15.4
Packing box size:	141×103×60mm	Frequency range:	2.405GHz~2.480GHz
Panel:	Tempered Crystal Glass	Receiving sensitivity:	-97dBm@250kbps
Bottom Materials:	Retardant PC	Operating temperature:	-25 degree to +60 degree
Rated voltage:	AC 100-250V 50/60Hz	Relative humidity:	<95%

## wiring diagram



## size diagram



## package



# L7 Light Switch (1GANG/2GANG/3GANG)



L7-HSM-B(Black)



L7-HSM-W(White)




L7-HSMU-B(Black)




L7-HSMU-W(White)

wiring diagram



size diagram



## Specification

Wireless Wi-Fi standard:	802.11b/g/n	Wireless Wi-Fi Security:	WEP/WPA/WPA2 (AES-TKIP-Personal)
Size:	85×85×32mm	Rated Load:	200W/GANG
Item no:	L7-HSM/L7HSMU	Load type:	Incandescent lamp, energy saving lamp, fluorescent
Weight:	0.3kg	Wireless standards:	IEEE 802.15.4
Packing box size:	141×103×60mm	Frequency range:	2.405GHz~2.480GHz
Panel:	Tempered Crystal Glass	Receiving sensitivity:	-97dBm@250kbps
Bottom Materials:	Retardant PC	Operating temperature:	-25 degree to +60 degree
Rated voltage:	AC 100-250V 50/60Hz	Relative humidity:	<95%

package



# L7 Curtains Control Switch



L7-HC-B(Black)



L7-HC-W(White)




L7-HCU-B(Black)




L7-HCU-W(White)

wiring diagram



size diagram



## Specification

Size:	85×85×32mm/120×74×32mm	Rated Load:	200W
Item no:	L7-HC/L7-HCU	Load type:	horizontal curtain motor/vertical curtain motor/electric door ect.
Weight:	0.3kg	Wireless standards:	IEEE 802.15.4
Packing box size:	141×103×47mm	Frequency range:	2.405GHz~2.480GHz
Panel:	Tempered Crystal Glass	Receiving sensitivity:	-97dBm@250kbps
Bottom Materials:	Retardant PC	Operating temperature:	-25 degree to +60 degree
Rated voltage:	AC 100-250V 50/60Hz	Relative humidity:	<95%

package



# L8

# MAGICPANEL LCD

## WIFI MESH SMART SWITCH

### AN UNPRECEDENTED INTERACTIVE EXPERIENCE

LCD SMART SWITCH

SUPPORT CUSTOMIZE BUTTON ICON. CHANGE NAME.

5 MODEL IN ONE SWITCH



# L8 Four gang Switch

## L8-HS4 (Four gang switch)



EUR standard-White



EUR standard-Black



USA standard-White




USA standard-Black


### Product parameters

Size:	86×86mm/120×74mm
Item no:	L8-HS4
Weight:	0.3kg
Packing box size:	102.6mm*141mm*51.1mm
Panel:	Capacitive touch screen
Bottom Materials:	Retardant PC
Rated voltage:	AC 100-250V 50/60Hz
Rated Load:	200W
Load type:	Incandescent lamp, energy saving lamp, fluorescent
Wireless standards:	IEEE 802.11b/g/n
Frequency range:	2.405GHz~2.480GHz
Receiving sensitivity:	-97dBm@250kbps
Operating temperature:	-25 °C +60 °C
Relative humidity:	<95%

### Wiring Diagram



### Size Diagram



### Package



# L8 Dimmer switch

## L8-HD (Dimmer switch)



EUR standard-White



EUR standard-Black



USA standard-White




USA standard-Black


### Product parameters

Size:	86×86mm/120×74mm
Item no:	L8-HD
Weight:	0.3kg
Packing box size:	102.6mm*141mm*51.1mm
Panel:	Capacitive touch screen
Bottom Materials:	Retardant PC
Rated voltage:	AC 100-250V 50/60Hz
Rated Load:	100W
Load type:	Incandescent lamp, LED lamp
Wireless standards:	IEEE 802.11b/g/n
Frequency range:	2.405GHz~2.480GHz
Receiving sensitivity:	-97dBm@250kbps
Operating temperature:	-25 °C +60 °C
Relative humidity:	<95%

### Wiring Diagram



### Size Diagram




### Package




# L8 Led Light Strip Smart Switch

## L8-HLS (Led Light Strip Smart Switch)




### Product parameters

Size:	86×86mm/120×74mm
Item no:	L8-HLS/L8-HLSU
Weight:	0.6kg
Packing box size:	102.6mm*141mm*51.1mm
Panel:	Capacitive touch screen
Bottom Materials:	Retardant PC
Rated voltage:	AC 100-250V 50/60Hz
Rated Load:	200W
Load type:	No limited for water heater brand
Wireless standards:	IEEE 802.11b/g/n
Frequency range:	2.405GHz~2.480GHz
Receiving sensitivity:	-97dBm@250kbps
Operating temperature:	-25 °C +60 °C
Relative humidity:	<95%





# L8 Fan Smart Switch


## L8-HF (Fan smart switch)



### Product parameters


Size:	86×86mm/120×74mm
Item no:	L8-HF
Weight:	0.3kg
Packing box size:	102.6mm*141mm*51.1mm
Panel:	Capacitive touch screen
Bottom Materials:	Retardant PC
Rated voltage:	AC 100-250V 50/60Hz
Rated Load:	20W
Load type:	No limited for water heater brand
Wireless standards:	IEEE 802.11b/g/n
Frequency range:	2.405GHz~2.480GHz
Receiving sensitivity:	-97dBm@250kbps
Operating temperature:	-25 °C +60 °C
Relative humidity:	<95%






## L8 4 inch control center panel

L8-HP4 (4 inch control center panel)



### Product parameters

Size:	86mm×86mm×11mm
Item no:	L8-HP4
Resolution:	480*480
Display:	4-inch capacitive touch screen
Power Rating:	50W
Power Input:	AC110-250V
Frequency range:	2.405GHz~2.480GHz
Receiving sensitivity:	-97dBm@250kbps
Operating temperature:	-25 °C +60 °C
Relative humidity:	<95%
Other Functions:	Tuya Zigbee Gateway




# Dimmable light and color

The white light, color light and scene lighting effects of living room, bedroom and kitchen can be adjusted as required.




## L8 7 inch control center panel



### Product parameters


Size:	235mm*112mm*11mm
Item no:	L8-HP7
Display:	1280*800
Interface:	RJ45,RS485
Rated voltage: :	AC110-250V
Wireless standards:	IEEE 802.11b/g/n
Frequency range:	2.405GHz~2.480GHz
Receiving sensitivity:	-97dBm@250kbps
Operating temperature:	-25 °C +60 °C
Relative humidity:	<95%
Other Functions:	Tuya Zigbee Geteway



# L8X Split Touch Smart Switch

**L8X IS A COMPLETE SMART HOME SYSTEM**

L8X SERIES INCLUDES 1/2/3 GANG LIGHT SWITCH / 4 GANG LIGHT SWITCH / DIMMER SWITCH / CURTAINS CONTROL SWITCH / BOILER SWITCH / SCENE SWITCH . YOU CAN EASILY BUILD A COMPLETE SMART HOME.



# L8X 1 Gang Smart Switch



L8X-HS1-B(Black)



L8X-HS1-W(White)




L8X-HSU1-B(Black)




L8X-HSU1-W(White)

PRODUCT PARAMETERS	
SIZE:	86mm*86mm/120mm*74mm
ITEM NO:	L8X-HS1/L8X-HSU1
WEIGHT:	0.3kg
PACKING BOX SIZE:	141mm*102.5mm*52mm
PANEL:	Tempered crystal glass
BOTTOM MATERIALS:	Retardant PC
RATED VOLTAGE:	AC 100-250V 50/60Hz
RATED LOAD:	200W
LOAD TYPE:	Incandescent lamp, energy saving lamp, fluorescent
WIRELESS STANDARDS:	IEEE 802.11b/g/n
FREQUENCY RANGE:	2.405GHz~2.480GHz
RECEIVING SENSITIVITY:	-97dBm@250kbps
OPERATING TEMPERATURE:	-25 °C +60 °C
RELATIVE HUMIDITY:	<95%

## Wiring Diagram



## Size Diagram



## Package



# L8X 2 Gang Smart Switch



L8X-HS2-B(Black)



L8X-HS2-W(White)




L8X-HSU2-B(Black)




L8X-HSU2-W(White)

PRODUCT PARAMETERS	
SIZE:	86mm*86mm/120mm*74mm
ITEM NO:	L8X-HS2/L8X-HSU2
WEIGHT:	0.3kg
PACKING BOX SIZE:	141mm*102mm*52mm
PANEL:	Tempered crystal glass
BOTTOM MATERIALS:	Retardant PC
RATED VOLTAGE:	AC 100-250V 50/60Hz
RATED LOAD:	200W
LOAD TYPE:	Incandescent lamp, energy saving lamp, fluorescent
WIRELESS STANDARDS:	IEEE 802.11b/g/n
FREQUENCY RANGE:	2.405GHz~2.480GHz
RECEIVING SENSITIVITY:	-97dBm@250kbps
OPERATING TEMPERATURE:	-25 °C +60 °C
RELATIVE HUMIDITY:	<95%

## Wiring Diagram



## Size Diagram



## Package



# L8X 3 Gang Smart Switch



L8X-HS3-B(Black)



L8X-HS3-W(White)




L8X-HSU3-B(Black)




L8X-HSU3-W(White)

PRODUCT PARAMETERS	
SIZE:	86mm*86mm/120mm*74mm
ITEM NO:	L8X-HS3/L8X-HSU3
WEIGHT:	0.3kg
PACKING BOX SIZE:	141mm*102mm*52mm
PANEL:	Tempered crystal glass
BOTTOM MATERIALS:	Retardant PC
RATED VOLTAGE:	AC 100-250V 50/60Hz
RATED LOAD:	200W
LOAD TYPE:	Incandescent lamp, energy saving lamp, fluorescent
WIRELESS STANDARDS:	IEEE 802.11b/g/n
FREQUENCY RANGE:	2.405GHz~2.480GHz
RECEIVING SENSITIVITY:	-97dBm@250kbps
OPERATING TEMPERATURE:	-25 °C +60 °C
RELATIVE HUMIDITY:	<95%

## Wiring Diagram




## Size Diagram




## Package



# L8X 4 Gang Smart Switch



L8X-HS4-B(Black)



L8X-HS4-W(White)




L8X-HSU4-B(Black)




L8X-HSU4-W(White)

PRODUCT PARAMETERS	
SIZE:	86mm*86mm/120mm*74mm
ITEM NO:	L8X-HS4/L8X-HSU4
WEIGHT:	0.3kg
PACKING BOX SIZE:	141mm*102mm*52mm
PANEL:	Tempered crystal glass
BOTTOM MATERIALS:	Retardant PC
RATED VOLTAGE:	AC 100-250V 50/60Hz
RATED LOAD:	200W
LOAD TYPE:	Incandescent lamp, energy saving lamp, fluorescent
WIRELESS STANDARDS:	IEEE 802.11b/g/n
FREQUENCY RANGE:	2.405GHz~2.480GHz
RECEIVING SENSITIVITY:	-97dBm@250kbps
OPERATING TEMPERATURE:	-25 °C +60 °C
RELATIVE HUMIDITY:	<95%

## Wiring Diagram



## Size Diagram



## Package



# L8X Dimmer Switch



L8X-HD-B(Black)



L8X-HD-W(White)




L8X-HDU-B(Black)




L8X-HDU-W(White)

PRODUCT PARAMETERS	
SIZE:	86mm*86mm/120mm*74mm
ITEM NO:	L8X-HD/L8X-HDU
WEIGHT:	0.3kg
PACKING BOX SIZE:	141mm*102mm*52mm
PANEL:	Tempered crystal glass
BOTTOM MATERIALS:	Retardant PC
RATED VOLTAGE:	AC 100-250V 50/60Hz
RATED LOAD:	200W
LOAD TYPE:	LED light , Incandescent Lamp
WIRELESS STANDARDS:	IEEE 802.11b/g/n
FREQUENCY RANGE:	2.405GHz~2.480GHz
RECEIVING SENSITIVITY:	-97dBm@250kbps
OPERATING TEMPERATURE:	-25 °C +60 °C
RELATIVE HUMIDITY:	<95%

## Wiring Diagram



## Size Diagram



## Package



# L8X Curtains Control Switch



L8X-HC-B(Black)



L8X-HC-W(White)




L8X-HCU-B(Black)




L8X-HCU-W(White)

PRODUCT PARAMETERS	
SIZE:	86mm*86mm/120mm*74mm
ITEM NO:	L8X-HC/L8X-HCU
WEIGHT:	0.3kg
PACKING BOX SIZE:	141mm*102mm*52mm
PANEL:	Tempered crystal glass
BOTTOM MATERIALS:	Retardant PC
RATED VOLTAGE:	AC 100-250V 50/60Hz
RATED LOAD:	200W
LOAD TYPE:	Horizontal curtain motor/vertical curtain motor/electric door ect.
WIRELESS STANDARDS:	IEEE 802.11b/g/n
FREQUENCY RANGE:	2.405GHz~2.480GHz
RECEIVING SENSITIVITY:	-97dBm@250kbps
OPERATING TEMPERATURE:	-25 °C +60 °C
RELATIVE HUMIDITY:	<95%

## Wiring Diagram



## Size Diagram



## Package

