

SL-FX2835CC24-120 (IC)

Coded	: SL-FX2835CC24-120 (IC)
LED Type	: SMD2835
Life time	: 30000 Hrs.
CRI	: >Ra 80 Normal
CCT	: 3000K, 4200K, 6500K
System Efficacy	: 140LM/M
LEDs/M	: 120LED
FPCB/mm	: 8mm.
Input Voltage	: DC 24VDC
System Power Consumption	: 14W/m
IP Rating	: 20
Operating Temperature	: -20°~50°C
Package	: 5M./Roll



SL-FX2835CC24-120 (IC)

Input Voltage	: 24V
Lumens /m	: 450Lm
Beam Angle	: 120°
CRI	: >Ra 80 Normal
CCT	: CCT / 2700K-6500K
Light efficiency	: 37.5
Leds/m	: 60
Tape width	: 12mm
Cutting step	: <5
Tc Temperturel	: <80°C
Protection Class	: IP20/IP65/IP67
Temp. Range	: -35°C ~ 50°C
Strip length per reel	: 5m / 10m

◀ Tunable White ▶



SL-FPE087E2-72L-RGBW

Lumen package	: 920lm
Max Length	: 15m
Light efficiency	: 37.5
CRI	: >Ra 80 Normal
CCT	: RGBW
Voltage	: 24V
LEDs/M	: 72LED
Tape width	: 10mm.
Waterproof grade	: IP20
Tc Temperture	: <80°C
Operating Temperature	: -35°C ~ 50°C
Beam Angle	: 120°
Strip length per reel	: 10m

◀ 16 Million colcrs ▶



SL-FX5050C6-72L-24V-RGBCCT

Lumen package	: 450lm
Max Length	: 15m
CCT	: RGBCCT
CRI	: >Ra 80 Normal
Light efficiency	: 37.5
Leds/m	: 72
Voltage	: 24V
Tape width	: 12mm.
Cutting step	: <5
Waterproof grade	: IP20
Tc Temperture	: <80°C
Operating Temperature	: -35°~50°C
Strip length per reel	: 5M-10M/Roll

◀ Tunable White ▶

◀ 16 Million colcrs ▶

